
LONGHAUL 202

ASPHALT RELEASE AGENT

Forms a tight coating that adheres to the surfaces of truck beds, drag slats, tools and other metal or rubber surfaces. This coating creates a barrier to prevent asphalt build-up, resulting in significant cost savings to your company.



LONGHAUL 202 ASPHALT RELEASE AGENT

DESCRIPTION

It is a vegetable based, biodegradable product for the asphalt and construction industry, LongHaul 202 forms a tight coating that adheres to the vertical surfaces of truck beds, drag slats, tools and other metal or rubber surfaces. This coating creates a barrier to prevent asphalt build-up, resulting in significant cost savings to your company.

DIRECTIONS FOR USE

Recommended usage level varies depending on application and requirement. Good starting point for dilution is in the range of 1:10 to 1:25. For best results use a foaming applicator.

FEATURES

- Non-staining on aluminum, steel and copper
- Good solvency characteristics
- Compatible with most systems
- Phosphate-free
- Oil and hydrocarbon-free, biodegradable and will not plug-up spray equipment like other oil based products
- Non-flammable/combustible
- VOC compliant
- No harsh ingredients
- Not WHMIS regulated: considered safe (to use in facility)
- Ideal for WETTING & RELEASE AGENT

IMPORTANT ADVICE

Do not mix with anything except water!

SAFETY INFORMATION

Eye Contact: Immediately flush with water for 15 minutes. Contact a physician immediately.
SKIN CONTACT: Immediately flush with water. Contact a physician if irritation develops.
INHALATION: Remove to fresh air. If symptoms persist, contact a physician.
INGESTION: Do not induce vomiting. Rinse mouth with water, then drink several glasses of water.
Contact a physician immediately.

PRODUCT DATA

pH range:	6.5 - 7.50
Appearance:	Amber liquid
Specific Gravity:	1.00 ± 0.001
Storage:	Store in original container in a cold, dry place away from incompatible materials.



Solutions Inc.

DIA SOLUTIONS INC. Oakville On. L6H 5Z9
(416) 907-2821 • (866) 518-5352