



Longhaul 220 – Asphalt Release Agent

1. IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND OF THE COMPANY

Identification of Preparation: Longhaul 220

Date of Safety Data Sheet: April 11, 2017

Use of Preparation: Asphalt Release Agent

Company Identification: Parkside Professional Products Ltd
4777 Kent Avenue
Niagara Falls, Ontario L2H 1J5
OFFICE: 905-358-8364

Company Emergency Telephone Number Emergency Phone: 905-358-8364

Transportation Emergency Telephone Number CANUTEC 613-996-6666 or * 666 for cell phone

2. HAZARD IDENTIFICATION

Emergency Overview:

OSHA / WHMIS 2015 Hazards

Irritant.

Classification of substance or mixture

GHS-US/Canadian classification:

GHS Hazards

Acute Toxicity 4 (Oral) H302

Eye Irritation 2 H319

Skin Irritation 2 H315

Label Elements

GHS Labelling

Hazard Pictograms (GHS):





Longhaul 220 – Asphalt Release Agent

Signal Word (GHS): Warning

Hazard Statements (GHS):

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary Statements (GHS):

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash thoroughly after handling.

Response (GHS):

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Description: Chemical Blend

Ingredient	CAS#	% by Wt	Classification
Sodium Laureth Sulphate	68891-38-3	7-13	Skin Irritation Category 2 A-H315 Eye Damage Category 1 - H318

4. FIRST AID MEASURES

Inhalation:	Remove to fresh air. If symptoms persist consult physician.
Eye Contact:	Remove contacts. Flush with water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Repeat if required. If irritation persists get medical attention.
Skin Contact:	Thoroughly wash exposed skin with soap and water. Remove any contaminated clothing and wash before reuse.
Ingestion:	Wash out mouth with water. Drink plenty of water. Do not induce vomiting unless directed by medical personal. Never give anything to an unconscious person. Get medical aid.
Notes to Physician:	Treatment based on judgment of attending physician.



Longhaul 220 – Asphalt Release Agent

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	As per surrounding fire.
Unsuitable extinguishing media:	No information available.
Special exposure hazards	Fire or excessive heat may produce hazardous decomposition products.
Special safety equipment:	Self-contained positive pressure breathing apparatus and protective clothing.
Fire and explosion	Not flammable. Not an explosive hazard.
Further information	Keep containers and surrounding cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe mist.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately by sweeping up and dispose of waste safely.

Reference to Other Sections: See Heading 8. Exposure controls and personal protection.

7. HANDLING AND STORAGE

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of mist.

Information about fire - and explosion protection:

Keep respiratory protective device available.

No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.



Longhaul 220 – Asphalt Release Agent

Information about storage in one common storage facility:

Do not store together with acid products.

Store away from reducing agents.

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Specific end use(s) No further relevant information available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection:	Use local exhaust or dilution ventilation.
Hand protection:	Chemical resistant gloves.
Eye protection:	Safety goggles.
Skin protection:	Use body-covering clothing.
Working hygiene:	Take usual precautions when handling. Workers should wash hands before eating, drinking or smoking.

Exposure Guidelines:

Source Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³
None.				

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Appearance	Colour	Property	Values	Odour	Odour Threshold	Remarks/Method
Liquid	Clear	Amber			Mild		
						No data available.	
pH	7.0-8.50				None known		
Melting/Freezing Point	No data available				None known		
Boiling Point/Range	No data available				None known		
Flash Point	Not applicable.				None known		
Evaporation Rate	No data available				None known		
Flammability (solid, gas)	Not flammable				None known		
Flammability Limit in Air:							
Upper Limit	No data available				None known		
Lower Limit	No data available				None known		



Longhaul 220 – Asphalt Release Agent

Vapour Pressure	No data available	None known
Vapour density	No data available	None known
Specific Gravity	1.0-1.01 g/cm ³	
Water Solubility	Soluble in water.	None known
Solubility Other Solvents	No data available	None known
Partition Coefficient:		
n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition Temperature	No data available	None known
Kinematic Viscosity	No data available	None known
Dynamic Viscosity	No data available	None known
Explosive Properties	No data available	None known
Oxidizing Properties	No data available	None known

Other Properties:

Softening Point	No data available
VOC Content %	No data available
Particle Size	No data available
Particle Size Distribution	No data available

10. STABILITY AND REACTIVITY

Reactivity	Stable at normal ambient temperature and pressure.
Chemical stability	No decomposition if stored and applied as directed.
Thermal decomposition/conditions to avoid:	Stable under normal conditions.
Possibility of hazardous reactions	Reacts with acids. Reacts with reducing and oxidizing agents.
Conditions to avoid	Store away from reducing agents, water, acids, and acid salts of heavy metals, organic materials and flammable substances.
Hazardous decomposition products	Acids, oxidizing and reducing agents.
Materials to avoid	Oxides of carbon.
Hazardous polymerization	Will not occur



Longhaul 220 – Asphalt Release Agent

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

Routes of Entry Inhalation, ingestion, eye or skin

Sodium salt of dodecyl benzene sulphonic acid CAS # 27176-87-0 :

LD50 (Oral) Rat: > 2,000 mg/kg

LD50 (Dermal) Rabbit: > 2,000 mg/kg

Carcinogenicity:

Chemical Name	ACGIH	IARC	NTP	OSHA
Not classified.				

Not classified.

IARC: (International Agency for Research on Cancer)

No ingredients listed

Chronic Effects:

Mutagenicity: No evidence of a mutagenic effect.

Teratogenicity: No evidence of a teratogenic effect (birth defect).

Sensitization: No evidence of a sensitization effect.

Reproductive: No evidence of negative reproductive effects.

Target Organ Effects:

Acute: No information available

12. ECOLOGICAL INFORMATION

Toxicity: Not classified

Persistence and Degradability: Not available

Bioaccumulative Potential: Not available

Mobility in Soil: Not available.

Other Adverse Effects

Other Information:

Avoid release to the environment.

All of the organic components of this product are readily biodegradable.

13. DISPOSAL

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Ecology – Waste Materials: Avoid release to the environment.



Longhaul 220 – Asphalt Release Agent

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation (DOT): Not Regulated

Canadian TDG (Road & Rail): Not Regulated

Water Transportation (IMO): Not Regulated

Air Transportation (IATA): Not Regulated

15. REGULATION

Occupational Health & Safety Regulations:

WHMIS Classification: Class D - Division 2B.



OSHA & WHMIS: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) and Canadian WHMIS regulations (Controlled Products Regulations under the Hazardous Products Act).

International Inventories

TSCA	-
DSL/NDSL	-
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	-
PICCS	-
AICS	Complies

Legend:

TSCA - All components of this product are listed or are exempt or excluded from listing on the United States Toxic Substances Control Act Section 8(b) Inventory.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances **ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances



Longhaul 220 – Asphalt Release Agent

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

HMIS III Rating:

Health: 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability: 0 Minimal Hazard

Physical: 0 Minimal Hazard

Personal Protection: B

SDS US (GHS HazCom 2012) SDS Canada (GHS WHMIS 2015)



Longhaul 220 – Asphalt Release Agent

16. OTHER INFORMATION

Prepared By: Parkside Professional Products Ltd
4777 Kent Avenue
Niagara Falls, Ontario L2H 1J5
905-358-8364

Issuing Date: April 11, 2017

Disclaimer:

The manufacturer warrants that this product conforms to its standard specification when used according to direction. To the best of our knowledge the information contained herein is accurate. However we do not assume accuracy or completeness of the information contained herein.

Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

End of Safety Data Sheet