



LONGHAUL 302

CONCRETE RELEASE AGENT

Intended as a concrete form release formulated from renewable materials. The product was developed for water based systems which are designed to work with steel and plywood forms.

Longhaul 302 can be used as supplied or incorporated into formulations.

DIRECTIONS FOR USE

Recommended usage level varies depending on application and requirement. Good starting point for dilution is in the range of 1:10 to 1:25. For best results use a foaming applicator.

FEATURES

- Free from petroleum based oils and solvents
- Water-soluble
- Zero VOC
- Effective for steel and plywood forms
- Excellent wetting allows for easy spray or brush applications
- Provides smooth uniform releases with no staining and minimal surface voids in the concrete
- Does not affect curing process
- Stable after exposure to low temperatures (-34 °C)

IMPORTANT ADVICE

Do not mix with anything except water!

STORAGE INFORMATION

The product should be stored in ambient indoor storage conditions, avoiding extreme heat or freezing.

Skin Contact: Immediately flush with water. Contact a physician if irritation develops. Inhalation: Remove to fresh air. If symptoms persist, contact a physician. Ingestion: Do not induce vomiting. Rinse mouth with water, then drink several glasses of water. Contact a physician immediately.

PRODUCT DATA

Appearance:	Amber liquid
Density, mg/l 1.02	1.00 ± 0.01



Solutions Inc.

DIA SOLUTIONS INC. Oakville On. L6H 5Z9
(416) 907-2821 • (866) 518-5352